

# Handheld Isotope Identification Instrument RIID RT-30 Mk II series

The RT-30 Mk II is the second generation of popular handheld gamma ray spectrometer RT-30. Strengths of the first generation were copied in the new model. There has to be highlighted a strong alloy body sealed against dust and water, protective removable rubber boot, comfortable grip and



### Applications

- *Homeland Security and surveillance operations*
- *Customs and Border protection*
- *Hospitals and Health physics*
- *Nuclear facilities*
- *Waste Recycling and Incineration plants*
- *Scrap metal recycling*
- *Research laboratories*
- *Production facilities*

low weight. The Mk II learned of the limitations of the first generation and features a large colored transreflective sun readable display,

improved user's interface with five operation buttons, removable but well-sealed battery pack and clear and loud audio.

The instrument is built as an open platform with potential of fast and simple implementation of special features required by customers. Wide fleet of detectors is supported. The Mk II bridges traditional scintillation detection probes using common vacuum photomultiplier tube with up-to-date silicon photomultipliers technology. Saved significant volume of vacuum tubes is next occupied by **larger size of detector**.

- *Excellent Sensitivity*
- *Highest ratio detector to unit volume*
- *Fast and Reliable Isotope Identification*
- *Lightweight, Rugged and Compact design*
- *Easy Operation*
- *Automatic Stabilisation on Natural background*
- *USB C and wireless connections*
- *Weather protected*
- *2-Year Warranty*

A heart of gamma ray spectrometer is FPGA (programmable array) plus fast speed and low consumption ARM type processor. The combination of FPGA with ARM is taken of preceding larger instrument and has been tested for years. Beside gamma ray section the FPGA is capable to handle other sensors at the same time. A Geiger-Mueller counter and a Neutron detector make a standard offer.

Thanks to latest electronic the Mk II opens a platform for supporting most modern existing communication standards. Sharing new and traditional communication standards is guaranteed wide compatibility with older as well as new communication devices. The existing USB was upgraded to level C and beside communication it is used also for unit's battery charging. GPS system is built in the front part of the instrument and is used for localization of the unit and

also for time synchronization.

Quickly determining the location of lost radioactive sources in the environment or scrap, monitoring of waste in hospitals or waste incinerators, scanning people or baggage to disclose illicit trafficking of nuclear materials; all are typical applications for the RT-30 Mk II series.

**GEORADIS**

**Features:**

- Ergonomic, lightweight handheld well balanced, compact
- Comfortable grip with five buttons operable in glows
- Removable protective rubber boot
- Detectors fully build in the housing, protected by rubber foam
- Large, transreflectible colored display - sharp and high contrast in sunlight, backlighted in dark
- Loudspeaker with plastic membrane watertight
  
- Four status indication LEDs – indication of alarms and health status
- USB standard C for data transfer and charging
  
- Wide fleet of scintillation detectors NaI/Tl, CsI/Tl, CsI/Eu, LaHalide, BGO, GAGG, Srl, Plastic scintillation detectors PVT
- Maximum detector size: Diameter 2” and height 2” with standard vacuum PMT or max 5” with Silicon PMT (SiPM or MPPC)

**Gamma Ray spectrometer with full digital signal evaluation**

- Fast sampling - 40 Mega sample/sec
- Pulse shape auto calibration - easy adaptation to different type of detectors
- Standard energy range 20 keV - 3 MeV in 1024 channels. Linear transition between energy and channel position. Linearization made on one million of microchannels using a lookup table.
- Energy range extendable up 10 MeV
- Progressive gain adjustment using NORM pattern with range overlap. Gain adjustment performed by a proportional backstage process regardless of working mode.
- Detailed and complex gain stabilization log for arbitrary reasons and long-term performance check.



**Search Mode – Survey Meter**

- Used for a source of radiation localization. Indication of intensity by gamma rate total counts or counts within predefined energy windows, dose rate, accumulated dose and neutron flux
- Scanned profile recorded on histogram. Anomalies highlighted by colors. Browsing capability of recorder within one recording session
- Waterfall screen mode for indication of intensities within spectrum
- Adjustable alarm thresholds for gamma rate, dose and dose rate
- Neutron warning active within all modes since unit is on
- Measured values integration and averaging mode - running average
- Loud acoustic indication of level of radiation
- Thresholds for acoustic indication and highlighting colors of recorder auto adjustable from actual background

- *Survey Meter*
- *Dose Rate Meter*
- *1024 Ch Spectrometer*
- *Highly Sophisticated Algorithms*
- *Automatic Stabilisation on Natural background*

**GEORADIS****Nuclide Identification Mode**

- Sensitive Gaussian filtering, doublet recovery algorithm
- Default and user customizable nuclide libraries, improved identification rules
- Found peaks listed with details about resolution, intensity and position
- Contribution power of Identified nuclides in blends rated by intensities
- Nuclide categories by their origin (Industrial, NORM, Medical, SNM)
- No limit on number of items in nuclide library

**NORM Assay Mode**

- Evaluation of concentrations of NORMs by least square fitting
- Two calibrations - default and user editable
- Results in form value and determined standard deviation
- Capable to determine concentrations (activities) of up to 6 nuclides in a blend
- Information about quality of a measured spectrum
- Spectrum drift correction

**Special Mode**

- Extended Energy Range Mode
- Energy range of gamma spectrum expandable up to 10 MeV
- Pulse time capturing system
- Variable look up tables

**Detector options:**

- SiPM scintillation detector with silicon photo multiplier
- L1, L2, L3, L4, L5 customized height of detector (1, 2, 3, 4 and 5 "). L3 to L5 only with SiPM
- T telescopic extension for gamma and GM detector
- NaI, CsI and BGO as common, other types as GAGG, YAP, Srl, LaH, PVT customized



## RT-30 Mk II Product Range

The RT-30 Mk II series has an IP65 dust- and water resistant, lightweight alloy milled housing and a detachable plastic boot for additional protection under harsh environments. The unit is powered by a removable Li-ION battery pack. A fully automatic charger is integrated in the unit. One plug in connector USB-C for data transfer and charging.

Standard Comparison Table		RT-30MKII	RT-30MKII T	RT-30MKII G	RT-30MKII GT	RT-30MKII N	GT-30MKII	GT-32MKII	RT-30MKII SiPM	RT-30MKII T SiPM	RT-30MKII N SiPM	GT-30MKII SiPM
Display	Numerical											
	Graphical	•	•	•	•	•	•	•	•	•	•	•
Data acquisition	Gross Counting	•	•	•	•	•	•	•	•	•	•	•
	Spectroscopy	•	•	•	•	•	•	•	•	•	•	•
Connectivity	USB C	•	•	•	•	•	•	•	•	•	•	•
	Bluetooth and Wi-Fi	•	•	•	•	•	•	•	•	•	•	•
	Large (32Gb)	•	•	•	•	•	•	•	•	•	•	•
Software	GeoView Package	•	•	•	•	•	•	•	•	•	•	•
	Isotope Identification	•	•	•	•	•			•	•	•	
	Assay mode						•	•				•
Detector type	NaI, 30 x 30mm											
	NaI, 51 x 51mm	•	•	•	•	•	•					
	NaI, 51 x max 120 mm								•	•	•	•
	BGO, 51 x 51mm						•					
	Alternative det. type								•	•	•	
	GM tube			•	•	•						•
Mechanical	Handheld	•		•		•	•	•	•		•	•
	Telescopic arm		•		•					•		

### Common Features

- Large scintillator, selectable type
- Advanced GUI operation
- Automatic Stabilisation on Natural background
- Selectable acoustic and visual alarm threshold, LED indication
- Sophisticated Nuclide Identification procedures
- Bluetooth and Wi-Fi communication, Ethernet connectivity
- Built in GPS, Glonass
- 32Gb internal memory
- Lightweight, robust design
- Optional Telescopic arm, Integrated GM tube or Neutron Detector
- LCD Graphic colour display transreflective
- Removable protecting boot
- Replaceable battery pack

## Technical data

### Detectors

Standard option

Nal/(TI),  $\Phi 51 \times 51$  mm (2" x 2"), 104 cm<sup>3</sup> (6.3 in<sup>3</sup>), all RT models  
BGO,  $\Phi 51 \times 51$  mm (2" x 2"), 104 cm<sup>3</sup> (6.3 in<sup>3</sup>), GT-32 Mk II model  
Photomultiplier diameter 2", bialkali

Energy compensated GM tube with RT-30 Mk II G, RT-30 Mk II GT and RT-30 Mk II N  
He-3 Neutron tube with RT-30 Mk II N

Special option

CsI/(TI), CsI/Eu, LaH, Srl, GAGG, YAP ,  $\Phi 51 \times \max 120$  mm (2" x max 5"), SiPM array

### Spectrometer

1024 channel, 40 MHz DSP, Linear Energy corrected  
Pile-up Rejector, 200 ns Resolution  
Energy range 20keV - 3,0 MeV, expandable up 10 MeV

### Scintillometer

Sampling period 20/second  
Acoustic and video alarm, 4 LED indicators  
Moving average and integration

### Dose Meter

Energy corrected dose rate for Nal detector, H\*10  
Extended range with GM tube 100 mSv/h (10 R/hr)

### Gamma ray sensitivity at 1m (Nal/TI 2x2")

160 cps/1MBq for Cs-137  
75 cps/1MBq for Am-241  
270 cps/1MBq for Co-60

### Display

Colour LCD, 360 x 240 dots, 72 x 54 mm (3.5"), Sun readable  
Automatic Backlight

### Acoustic indication

audio frequency is proportional to measured count rate  
Speaker, dia. 28 mm + Built-in Microphone

### Control

Illuminated Navigation Joystick, 5 positions

### Data Storage and Transfer

32 GB memory for spectra, search profiles and dose, min. 8000 Samples with full Spectra, Data Position and Voice Message  
USB-C, direct and Ethernet mode, Bluetooth 1.2 Class 2 and Wi-Fi





**GEORADIS**

**GPS Support**

Internal - GNSS engine for GPS/QZSS, GLONASS, 56-channels  
 NMEA 0183  
 External GPS connectable

**Power**

Rechargeable Li-ion 7.2 V / 6600 mAh (Panasonic CGR18650CG/2S3P) – min. 8 hours of operation at 20°C  
 External AC adapter USB-C 60W for charging or measurement

**Environmental**

IP-65 Dust and Water resistant  
 Operating temperature range -10°C to +50°C  
 RFI/EMF Shielding complies with FCC(47 CFR part 15) for  
 Class A CE Certification

**Size and weight**

Size L x W x H 29 cm x 10 cm x 16 cm  
 Weight 3 kg

**Standard accessories:**

Carrying Durable Suitcase  
 Battery charger  
 GeoView Software  
 USB cable  
 User's guide  
 Calibration protocols

**Optional accessories:**

Shoulder Carrying Harness  
 Spare Battery Pack



Specifications are subject to change without notice

**GEORADIS**

Production and service: GEORADIS s.r.o.  
 Novoměstská 321/41  
 619 00 Brno, CZ  
 Phone: +420 541 422 236  
 Fax: +420 541 422 232  
 E-mail: info@georadis.com  
 Web: www.georadis.com

Distribution:

V1.01-2021-01-RT30 MkII

PEO B.V.

info@gotopeo.com  
 www.gotopeo.com

The Netherlands

Havenweg 16, 6603 AS Wijchen  
 +31 (0)24 648 86 88

Belgium

Watermolenstraat 2, B-2910 Essen  
 +32 (0)3 309 32 09

CoC 34107894

VAT NL807859151B01

IBAN NL29 RABO 0356 1960 46

BIC RABONL2U

